

ELKA

designer floors for living

110mm SOLID NATURAL MAPLE FLOORING



Lacquered

Appearance General

Colour:

- Heartwood is creamy white to light reddish brown; sapwood is pale to creamy white.

Grain:

- Closed, subdued grain, with medium figuring and uniform texture. Occasionally shows quilted fiddleback, curly or bird's-eye figuring.

Variations Within Species And Grades:

- High variation among boards in colour and grain texture giving unique character

Specification:

- Grade: 'A-B-C'
- Maple origin: USA
- Timber: Plainsawn
- Pack Size: 1.056 M2
- 18x110mm Random lengths 300 - 1200MM, Average 630MM
- Lacquer : 6 base coats and 2 top coats
- Sheen: 40% Satin
- Lacquer brand: Treffert, German brand
- FSC/PEFC certificate: No
- Janka score: 1450

Workability

Installation:

- Professional & Fixed recommended

Sanding:

- Good if the correct sanding sequence is followed

Installing methods allowed:

- Nailing on to Wooden Sub-Floor
- Gluing on to Wooden or Concrete Sub-Floor
- Direct to joist (not recommended)

Must never do:

- Must not be laid over under floor heating
- Must not be laid in a conservatory
- Must not be laid in bathrooms
- Must not be floated

Features and Advantages:

- Can be sanded and re-finished
- 100% natural solid wood
- Ensures excellent thermal and acoustic isolation
- Floor can be laid in most residential areas (except those of high humidity)
- Elka Extras available – underlay, adhesives, finishing profiles & maintenance products. View these at www.elkaflooring.com

See www.elkaflooring.com for warranty information

