

## 130mm EUROPEAN OAK FLOORING



*Lacquered*

### **Appearance General**

#### **Colour:**

- Heartwood is light brown; some boards may have a pinkish tint or a slight greyish cast. Sapwood is white to cream.

#### **Grain:**

- Open, with longer rays than red oak. Occasional crotches, swirls and burls. Plain sawn boards have a plumed or flared grain appearance

#### **Variations Within Species And Grades:**

- Medium variation among boards in colour and grain texture.

#### **Specification:**

- Grade: Natural Grade 'A/B/C'
- Bevel: G4 0.5mm 'long & short edge'
- Pack Size: 1.248m<sup>2</sup>
- Oak origin: European
- 18x130mm Random lengths 300 – 1200mm - average 630mm
- Lacquer : 6 coats
- Sheen: 40% Satin
- Lacquer brand: Treffert, German brand
- FSC/PEFC certificate: No
- Janka score: 1360 'medium hardness'

### **Workability**

#### **Installation:**

- Professional recommended

#### **Sanding:**

- Good if the correct sanding sequence is followed

#### **Installing methods allowed:**

- *Nailing on to Wooden Sub-Floor*
- Gluing on to Wooden or Concrete Sub-Floor

#### **Must never do:**

- Must not be laid over under floor heating
- Must not be laid in a conservatory
- Must not be laid in bathrooms
- Must not be floated

#### **Features and Advantages:**

- Premium grade timber
- Can be sanded and re-finished
- 100% natural solid wood
- Ensures excellent thermal and acoustic isolation
- Floor can be laid in most residential areas (except those of high humidity)
- Elka Extras available – underlay, adhesives, finishing profiles & maintenance products. View these at [www.elkaflooring.com](http://www.elkaflooring.com)

See [www.elkaflooring.com](http://www.elkaflooring.com) for warranty information

