

ELKA

designer floors for living

130mm RUSTIC OAK FLOORING



Brushed & Oiled



Lacquered

Appearance General

Colour:

- Heartwood is light brown; some boards may have a pinkish tint or a slight greyish cast. Sapwood is white to cream.

Grain:

- Open, with longer rays than red oak. Occasional crotches, swirls and burls. Plain sawn boards have a plumed or flared grain appearance

Variations Within Species And Grades:

- Considerable variation among boards in colour and grain texture.

Specification:

- Grade: Rustic 'B-C-D'
- Moisture content: 8-10%
- Bevel: G4 1.2mm 'long & short edge'
- 18x130mm Random lengths 300 - 1700MM Average 680MM
- Timber: Plainsawn
- Pack Size: 2.184 m²
- UV Lacquer : 7 coats
- Sheen: 35% +/-5
- UV Oil: 1 base coat and 1 top coat
- Sheen: 15% +/-5
- Lacquer: PPG
- Oil brand: Treffert, German brand
- Janka score: 1360 'medium hardness'

Workability

Installation:

- Professional recommended

Sanding:

- Good if the correct sanding sequence is followed

Installing methods allowed:

- *Nailing on to Wooden Sub-Floor*
- Gluing on to Wooden or Concrete Sub-Floor
- Direct to joist providing boards are secured to a minimum of two joists

Must never do:

- Must not be laid over under floor heating
- Must not be laid in a conservatory
- Must not be laid in bathrooms
- Must not be floated

Features and Advantages:

- Can be sanded and re-finished
- 100% natural solid wood
- Ensures excellent thermal and acoustic isolation
- Floor can be laid in most residential areas (except those of high humidity)
- Elka Extras available – underlay, adhesives, finishing profiles & maintenance products. View these at www.elkaflooring.com

See www.elkaflooring.com for warranty information