

22mm UNFINISHED ENGINEERED FLOORING



Unfinished

Appearance General

Colour:

- Solid white oak
- Heartwood is light brown; some boards may have a pinkish tint or a slight greyish cast. Sapwood is white to cream.

Grain:

- Open, with longer rays than red oak. Occasional crotches, swirls and burls. Plain sawn boards have a plumed or flared grain appearance

Variations Within Species And Grades:

- High variation among boards in colour and grain texture giving unique character.

Specification:

- Grade: Rustic 'B\C\D'
- Oak origin: China
- Bevel: G4 0.5mm 'long & short edge'
- 22mm x 189 x 1860mm, 6mm top veneer
- Pack Size: 2.11 M2
- Finish: Knots filled and Sanded
- Core: Poplar
- Adhesive: : Melamine glue, China made, E1 environmental friendly
- FSC/PEFC certificate: No
- Janka score: 1360 'medium hardness'

Workability

Installation:

- Professional & Floating recommended

Sanding:

- Good if the correct sanding sequence is followed

Installing methods allowed:

- Floating over underlay
- Nailing on to Wooden Sub-Floor
- Direct to joist
- Gluing on to Wooden or Concrete Sub-Floor

Must never do:

- Must not be laid in bathrooms

Features and Advantages:

- Can be laid over under floor heating and in conservatories
- Can be sanded and re-finished
- Made 100% of natural wood
- Ensures excellent thermal and acoustic isolation
- Excellent dimensional stability
- Floor can be laid in all residential areas (except those of high humidity)
- Elka complimentary accessory products available – underlay, adhesives, finishing profiles & maintenance products. View these at www.elkaflooring.com

See www.elkaflooring.com for warranty